

Constructed from an extremely durable and lightweight metallised frame and featuring an interchangeable lens option, SISINI™ is an extremely robust and versatile option for the majority of applications.

## SPECIAL FEATURES

- ✓ Sports style design
- ✓ Dual moulded temples with TPE temple ends for maximum fit and comfort
- ✓ Soft adjustable PVC nose bridge
- ✓ Easy fit interchangeable lens option
- ✓ Polarised lens tint option available
- ✓ Supplied with a microfibre storage pouch
- ✓ Weight: 27g
- ✓ 8-Base lens



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	RLY00136	2C-1.2 e 1FKN CE	e EN 166 F CE	Impacts, UV radiations	TECTON 400 K&N Anti-scratch and Anti-fog / UV400 / Moisture repellent
AMBER	RLY00138	2C-1.2 e 1FKN CE	e EN 166 F CE	Impacts, UV radiations	
GREY	RLY00137	5-2.5 e 1FKN CE	e EN 166 F CE	Impacts, UV and Solar radiations	ARIDA Moisture Repellent + Anti-fog Riley Anti-scratch and Anti-fog
REVO	RLY00139	5-2.5 e 1F CE	e EN 166 F CE	Impacts, UV and Solar radiations	
POLARISED	RLY00140	5-3.1 e 1F CE	e EN 166 F CE	Impacts, UV and Solar radiations	

See overleaf for this product's technical specification 

## GENERAL SPECIFICATION

LENS BASE	8mm
WEIGHT	27g

## PACKAGING

Individually contained in a polythene bag with a Eurosot

PER BOX	10
PER CARTON	200

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Dual lens design
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	TR90 Thermoplastic/ Metal	Co-injected - Durable and flexible, with contour grip
HINGE	TR90 Thermoplastic/ Metal	Increased flexibility and strength


## LENS MARKINGS

### LENS FILTER TYPE:

2C UV  
5 Solar

### SCALE NUMBER (SHADE):

1.2 Clear or Amber  
2.5 Grey or Revo  
3.1 Dark Grey or Mirror

 Identity of manufacturer

### OPTICAL CLASS:

1 High optical quality

### MECHANICAL STRENGTH:


F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

### PERFORMANCE:

K Resistance to scratches by fine particles  
N Resistance to fogging

 Certification mark

## FRAME MARKINGS

 Identity of manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s

 Certification mark

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.