



The single wide-vision lens featured provides the wearer with an exceptional field of vision.

Lateral protection and a unique, flexible sidearm provide unrivalled comfort and grip. Weighing 21g,

### SPECIAL FEATURES

- ✓ Ultra-lightweight
- ✓ Single wide vision lens gives exceptional field of vision
- ✓ Lateral protection
- ✓ Uniquely flexible sidearms
- ✓ Supplied with a microfibre storage pouch
- ✓ Weight: 21g
- ✓ 9-Base lens



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	○ RLY00091	2C-1.2 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	TECTON K&N Anti-scratch and Anti-fog
AMBER	● RLY00093	2C-1.2 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	
GREY	● RLY00092	5-2.5 e 1FTKN CE	e EN 166 FT CE	Impacts, UV and Solar radiations	
BLUE	● RLY00095	5-1.7 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	
INDOOR/OUTDOOR	◐ RLY00094	5-1.7 e 1FT CE	e EN 166 FT CE	Impacts, UV radiations	ARIDA Moisture Repellent + Anti-fog

See overleaf for this product's technical specification



# Li.Bo

Safety

## GENERAL SPECIFICATION

LENS BASE	9mm
WEIGHT	21g

## PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	One piece moulded lens with side protection
NOSE BRIDGE	Moulded polycarbonate	One piece moulded universal
TEMPLE	TR90 Thermoplastic	Hard-wearing
HINGE	TR90 Thermoplastic/ Metal	Increased flexibility and strength


## LENS MARKINGS

### LENS FILTER TYPE:

2C UV  
5 Solar

### SCALE NUMBER (SHADE):

1.2 Clear or Amber  
2.5 Grey  
1.7 Minimises or I/O

 Identity of manufacturer

### OPTICAL CLASS:

1 High optical quality

### MECHANICAL STRENGTH:


F Low energy impact, resists a 6mm, 0.86g ball at 45m/s  
T Protection against high-speed particles at extreme temperatures

### PERFORMANCE:

K Resistance to scratches by fine particles  
N Resistance to fogging

 Certification mark

## FRAME MARKINGS

 Identity of manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s  
T Protection against high-speed particles at extreme temperatures

 Certification mark

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.